

VPL-VW1100ES/X

Sony 4K Home Theater ES Projector and Media Player Package

Experience Sony's most immersive, awe-inspiring home theater with the Sony 4K projector featuring SXRD™ 4K movie theater projector technology. Delivering greater than four times 1080p resolution, anamorphic 3D, and HD to 4K upscaling, nothing else comes close to the Sony® VPL-VW1100ES Projector. No detail was left out—including easy installation and control.



Bullets

- 4K resolution—4096x2160. That's greater than 4 times 1080p
- HD to 4K upscaling turns your HD content into a 4K experience
- 1,000,000:1 dynamic contrast ratio with SXRD™ technology
- Brightness of 2,000 ANSI lumens
- Control over RS232 or IP with feedback
- Flexible installation—2.1 motorized zoom, 80%(v)/30%(h) motorized shift and 1.27-2.73 throw

ratio

- HDMI® 2.0 compatible for 4K resolution at up to 60 frames per second
- 3-year limited warranty
- Picture position feature for lens-less anamorphic (2.35:1)
- Whisper-quiet fan
- Bundled with FMP-X1 4K UHD Media Player and Sony Tablet Z

Features

An astonishingly immersive home theater experience

Features the same technology and resolution found in high-end, professional 4K movie theaters, providing an astonishingly immersive home theater experience. 4K resolution is 4096x2160. That's more than 4 times 1080p. Add a 1,000,000:1 dynamic contrast ratio, 2,000 ANSI lumen brightness, and wide color gamut and the VPL-VW1100ES/X pulls you into your favorite movies like no home theater projector you've ever experienced.

Recommended for up to a 200" screen

Because the VPL-VW1100ES has such high resolution and brightness, you can install a 200" screen and still experience an astonishingly crisp and bright picture in 2D. (Up to 150" if you want to use 3D.)

Enjoy your favorite 1080p HD movies and shows in 4K

Watch your favorite HD movies and television shows in 4K with Reality Creation upscaling. Sony's proprietary Super Resolution algorithm makes your best video content look better than ever before. And Sony's proprietary "Mastered in 4K" algorithm faithfully reproduces specially prepared movies to match the original 4K images.

Get the most out of your Sony 4K projector

The included 4K Ultra HD Media Player allows you to enjoy 4K video shorts, and Sony's Video Unlimited 4K network video service provides access to a library of 4K movies and TV shows.³ Control it all with a Sony Tablet, both of which come with the VPL-VW1100ES/X.

Integrate into virtually any home automation system

Seamlessly integrate the VPL-VW1100ES/X into virtually any major automation system through the bi-directional, industrystandard RS232 or IP connections.

Simple installation

Installing the VPL-VW1100ES/X is easy with its motorized $2.1x \mod 80(v)/30$ (h) motorized shift and flexible throw distance -1.27-2.73 throw distance for 1.78:1 and 1.68-2.73 for 2.35:1 anamorphic zoom using the picture position feature.

No anamorphic lens required

When using a cinema scope screen, enjoy 2.35:1 content without the need for an external anamorphic lens using the Picture Position function.

SONY

Immersive, vibrant picture for any environment

By simply choosing the appropriate preset, the VPL-VW1100ES/X's 2,000 ANSI Im brightness and color gamut can be adjusted for the ideal picture quality in any environment—whether gaming or watching sports in a lit room, or enjoying movies in a dark theater.

Watch 2D high-definition content in 3D

Add a new dimension to your favorite movies, shows or videos with Sony's unique 2D to 3D upconversion algorithm, allowing high definition 2D content connected via HDMI® to be viewed in immersive Sony 3D.²

Whisper-quiet fan

Forget that the projector is even in the room. Due to the VPL-VW1100ES/X's advanced air discharge system.

Powerful picture calibration features

Quickly calibrate your picture to the type of content you're enjoying with nine unique modes including a variety of cinema, gaming, photo and user customizable pre-sets.

Automatic motorized lens protector

The lens cover of the VPL-VW1100ES/X opens automatically when the projector powers on, then closes when the projector is turned off to prevent dust build-up on the lens.

Integrated IR 3D Sync Transmitter

No need to wire an external transmitter. The built in IR transmitter can adequately cover home theaters with up to 130" screens at 0.85 gain.

153 Zone Panel Alignment

153 zone, 1/10th pixel step, panel alignment ensures a sharp image.

Smoother, sharper motion

Enjoy smooth, sharp motion with Sony's Motionflow™ technology with Dark Frame Insertion and 24p True Cinema technologies.

3-year limited warranty

Rest assured that Sony has you covered. All Sony Elevated Standard (ES) projectors enjoy 3-year limited warranties, including a special tech support hotline in case you run into any problems.

Specifications

3D Features		
3D Features	2D to 3D Conversion	Yes
	3D Glasses Brightness Adjustment	2 Modes, Standard and High
	Digitally Driven Panel	Yes
	Effect Adjustment(s)	Yes
	Format(s)	Frame Packing/ Side by Side/ Over-Under/Simulated 3D/ESPN 3D format/ 720p / 60 SBS
	Signal	(HDMI inputs only) 1080:24p/60p/50p/60i/50i ; 720:60p/50p
	Simulated 3D	Yes
	Transmitter	Built-in with the option for external
Convenience Features		

SONY

All of input Search Yes BRAVIAB Sync ^M Yes Convenience Features BRAVIAB Sync ^M Front & Rear Convenience Features Inage Fip HV H, V, Off Receiver Front & Rear Front & Rear Convenience Features Induction (Linguage Charlon (Linguages Charlon) Second (Linguages Charlon) Device Control Yes (RM-H222) Second (Linguages Charlon) Display Test Partern Yes Display Screen Size 60° 20'0' recommended Agent Ratio 17.9 Second (Linguages Charlon) Display Features Vest Controld Controle (Second (Linguages Charlon) Ceneral Display Features Vest Controld Controle (Second (Linguages Charlon) Ceneral Display Features Vest Controld Controle (Second (Linguages Charlon) Ceneral Features Information Partner Vest Controle (Second (Linguages Charlon) Ceneral Features Acceptable Computer Signal Hit Range Crisp Focus (ARC-F) Protection Picture Size 60° to 300° measured diagonaly Ceneral Features Information Menu Horizontal Control (Controle Control Co			
Image Fip HV, H, V, Off IR Receiver Front & Rear; Front, Rear; Multiple Language Display German and Chinese) Power Save Mode Ves Recolo Control Ves (RM-RI22) Task Pattern Ves Diplay German and Chinese) Base Control Ves Diplay German and Chinese) Diplay German and Chinese) Base Control Ves Diplay Resolution AK - 4096 x 2160 Diplay Resolution 4096 x 2160 (Full & K) Diplay Features General Operation Use State Resolution Operation Pictures Ves Control Certified, AMX Device Discovery, Crestron Integrated Partner, Sovant Partner in Escate Resolution General Information Menu Hold Nach Partner, Sovant Partner in Escate Resolution Conumar Excellence, RTIX dong ReS/Company			
Receiver Front & Rear, Front, Rear Convenience Features In liple Language Display Is language (including English, French, Spanish, Geman and Chinese) Power Save Mode Yes Remote Control Yes (RM-PL22) Test Pattern Yes Display Affive Resolution 4K - 4096 x 2160 Display Screen Size 40% 2000 recommended Aspect Ratio 17.9 2000 recommended Display Resolution 40% x 2100 full dk) 2000 recommended Display Resolution 40% x 2100 full dk) 2000 recommended Display Resolution 40% x 2100 full dk) 2000 recommended Display Resolution 40% x 2100 full dk) 2000 recommended Display Resolution 40% x 2100 full dk) 2000 recommended Ceneral Vest Control Conflied, AMX Device Discovery, Costron Integrated Partney, Sowant Partney in Exceedinge, RII & URC) Ceneral features Acceptable Computer Signals Ft.19 to 72 kHz, fv.48 to 92 Hz, fv. 60 Hz Information Menu Hotorated focus, still and zoon with servo/memory 20 and by Mode Renard Features If/V Tigger Outputfs Affichar P		· ·	
Convenience Features Multiple Language Display 15 languages (including English, French, Sponish, German and Chinese) Prover Save Mode Ves Remote Control Yes (RM-PJ22) Test Pattern Ves (RM-PJ22) Display Screen Size 60°-200° recommended Aspect Ratio 17:9 00% × 2160 (Full 4K) Display Features Display Resolution 40% × 2160 (Full 4K) Display Features Display Technology 20% RD/M Technology Ceneral Ves (Control 4 Certified, AMX Device Discovery, Creatron Integration Partner Creatron Integration Partner in Excellence, RTI & URC) General Integration Partner Ves (Control 4 Certified, AMX Device Discovery, Creatron Integrating Partner in Excellence, RTI & URC) General Features Integration Partner Ves (Control 4 Certified AMX Device Discovery, Creatron Integrating Partner in Excellence, RTI & URC) General Features Integration Partner Ves (Control 4 Certified AMX Device Discovery, Creatron Integration Partner in Strandby Computer Signals General Features Integration Partner Ves (Control 4 Certified AMX Device Discovery, Creatron Integration Partner in Strandby Mode General Features Integration Partner is strandby Mode Not is	Convenience Features	• •	HV, H, V, Off
Multiple Language Display Control Control Control Power Save Mode Yes Remote Control Yes (RM-PJ22) Test Pottern Yes Display Wes Display Kernet Pottern Display Mattive Resolution 4K - 4096 x 2160 Display Screen Size 60°-200° recommended Display Resolution 4096 x 2160 (Full 4K) Display Resolution Kall Range Crisp Resolution General Integration Partner Centeral Kall Range Crisp Resolution Resolution General Features Information Menu Hi 19 to 72 kHz fv: 48 to 92 Hz fv: 60 Hz General Features Information Menu		IR Receiver	Front & Rear, Front, Rear
Remote Control Yes (RM-RJ22) Display Fast Pattern Yes Display Mitrive Resolution 4K - 4096 x 2160 Display Resolution 60*200" recommended Display Resolution 60% 200" recommended Display Resolution 0506 x 2160 (Fuil 4K) Ceneral Visi (Controld Certified, AMX Device Discovery, Cristerion Integrated Pather, Savant Partner In Excellence, RII & URC) General Features Infegration Partner Yes (Controld Certified, AMX Device Discovery, Cristerion Integrated Pather, Savant Partner In Excellence, RII & URC) General Features Infegration Partner Yes (Controld Certified, AMX Device Discovery, Cristerion Integrated Pather, Savant Partner In Excellence, RII & URC) General Features Information Menu Holt Partner, Savant Partner In Excellence, RII & URC) General Features Information Menu Holt Partner, Savant Partner		Multiple Language Display	
Test Partern Yes Display Native Resolution 4K - 4096 x 2160 Display Screen Size 60°-200° recommended Aspect Ratio 17.9 Display Resolution 4096 x 2160 (Full 4k) Display Resolution 4096 x 2160 (Full 4k) Display Features Features Display Features Ves (Control4 Certified, ANX Device Discovery, Creatron Integrated Partner, Savant Partner in Excellence, R11 & URC) General Integration Partner Ves (Control4 Certified, ANX Device Discovery, Creatron Integrated Partner, Savant Partner in Excellence, R11 & URC) General Features KAI Range Crisp Focus (ARC-F) Projection Picture Size 60° to 300° measured diagonally General Features Information Menu Hortzontal and Vertical frequency display Input A Dusto IS Pin, Analog RGB/Component Instrumation Menu Input A Dusto IS Pin, Analog RGB/Component Savanty Mede Input A Dusto IS Pin, Analog RGB/Component Savanty Mede Input S and Outputs 12V Trigger Output(s) 4100hms Power On: DC 12V, output Impedance: 47.410hms Power On: DC 12V, output Impedance: 47.410hms Power On: DC 12V, output Impedance: 47.410hms Power On: DC 12V, output Impe		Power Save Mode	Yes
Display Native Resolution 4K-40% x 2160 Display Screen Size 60°-200° recommended Aspect Ratio 17.9 Display Resolution 40% x 2160 (Full 4K) Display Features Display Resolution 40% x 2160 (Full 4K) Organization With Connology SKRD ^{IM} Technology General Integration Partner Visi Control Confinition, AMX Device Discovery, Crestron Integrated Partner, Savant Partner In Excellence, RII & URC) General Integration Partner Visi Control Confinition, AMX Device Discovery, Crestron Integrated Partner, Savant Partner In Excellence, RII & URC) General Features Integration Partner Visi Control Confinition, Savant Partner In Excellence, RII & URC) General Features Acceptable Computer Signals ft: 19 to 72 kHz, IV: 48 to 92 Hz, IV: 60 Hz Information Menu Hortontal and Vertical frequency display Input A Display Mode Ves Input A Display Control 200 (File Size) Input A Display Partner Size Control Information Menu Hortontal and Vertical frequency display Input A Display Resolutin display (File Mastin display) <		Remote Control	Yes (RM-PJ22)
Native Resolution 4K - 4096 x 2160 Display Screen Size 60°-200° recommended Aspect Ratio 17.9 Display Resolution 4096 x 2160 (Full 4K) Display Features Display Resolution 4096 x 2160 (Full 4K) Display Features Display Technology SXRD™ Technology General Integration Partner Vest Controld Certified, AMX Device Discovery, Crestron Integrated Partner, Savant Partner in Excelence, R18 & URO; General Integration Partner Vest Controld Certified, AMX Device Discovery, Crestron Integrated Partner, Savant Partner in Excelence, R18 & URO; General Features Integration Partner K All Range Crisp Focus (ARC-F) Projection Picture Size 60° to 300° measured diagonally General Features Information Menu Hoi 2001 faquency display Input A Dsub 15 Pin, Analog RGB/Component Lens Control Lens Control Mol Vorized focus, shift and zoom with servo/memory anomyphic zoom); Standby Mode Ves Input S Sync 1 (Side) RJ45 Component Video (V/Pb/Pi) 2 (Side) Digital RGB/V/Cb(Pb)Cr(Pr) with PC timing supporti July Lingur S Input		Test Pattern	Yes
Bisplay Screen Size 60°-200° recommended Aspect Ratio 17.9 Display Resolution 996 x 2160 (Full 4K) Display Features U Display Features SIRD™ Technology General Integration Partner Vess (Controld Certified, AMX Device Discovery, Crestron Integrated Partner, Savant Partner in Excellence, R11 & URC) General Integration Partner Vess (Controld Certified, AMX Device Discovery, Crestron Integrated Partner, Savant Partner in Excellence, R11 & URC) General Features Integration Partner Vess (Controld Certified, AMX Device Discovery, Crestron Integrated Partner, Savant Partner in Excellence, R11 & URC) General Features Integration Partner Vess (Controld Certified, AMX Device Discovery, Crestron Integrated Partner, Savant Partner in Excellence, R11 & URC) General Features Acceptable Computer Signals Ft: 19 to 72 kHz, IN: 48 to 92 Hz, IN: 60 Hz Information Menu Horizontal and Vetrical frequency display General Features Information Menu Horizotal cous, shift and zoom with servo/memory anamorphic zoom, in and output Input A Desub 15 Pin, Analog RGB/Component Lang Couptor (Sing) Input S Syster Control Couptor (Sing) Side) Mini Jack	Display		
Display Aspect Ratio 17.9 Display Resolution 4096 x 2160 (Full 4K) Display Reatures Japlay Resolution 4096 x 2160 (Full 4K) Display Reatures Display Technology SXRD ^M Technology Ceneral Integration Partner Yes (Controld Certified, AMX Device Discovery, Crestron Integrated Partner, Savant Partner in Excellence, RI & URC) General Integration Partner Yes (Controld Certified, AMX Device Discovery, Crestron Integrated Partner, Savant Partner in Excellence, RI & URC) General Integration Partner Yes (Controld Certified, AMX Device Discovery, Crestron Integrated Partner, Savant Partner in Excellence, RI & URC) General Features All Range Crisp Focus (ARC-F) Excelence, RI & URC) General Features Acceptable Computer Signals ft: 19 to 72 kHz, fV: 48 to 92 Hz, tV: 60 Hz Information Menu Horizontal and Vertical frequency display Information Menu Horizontal and Vertical frequency display General Features Information Menu Horizot focus, shift and zoom with servo/memory General Features Information Menu Horizot focus, shift and zoom with servo/memory General Features Information Menu Horizot focus, shift and zoom with servo/memory		Native Resolution	4K - 4096 x 2160
Aspect Ratio 17.9 Display Readures 0 0.96 × 2160 (Full 4K) Display Feadures 0 SXRD ^M Technology SXRD ^M Technology Ceneral 1 Vest (Control/ Certified, AMX Device Discovery, Crestron Integrated Partner, Savant Partner in Excellence, RT & URC) General 1 Vest (Control/ Certified, AMX Device Discovery, Crestron Integrated Partner, Savant Partner in Excellence, RT & URC) General 1 4K All Range Crisp Focus (ARC-F) Projection Picture Size 60° to 300° measured diagonally General Features Acceptable Computer Signals fH: 19 to 72 kHz, tV: 48 to 92 Hz, tV: 60 Hz Information Menu Horizontal and Vertical frequency display Input A D-sub 15 Pin, Analog RGB/Component Lens Control Motorized focus, shift and zoom with serve/memory Standby Mode Ves Inputs and Outputs 2 Arx (side) RAG Inputs and Outputs 12V Trigger Output(s) 4.7 kitoms Power Oft: OV (Two, selectable power / arramorphic zoom,) 3D Sync 1 (Side) RI48 Component Video (Y/Pb/Pr) 2 (Side) Digital Rest/Y/Cb(Pb)Or(Ph)Ort(Ph) with PC timing support ¹ Inputs and Outputs	Disalari	Screen Size	60"-200" recommended
Display Features Display Technology SXRD ^{IM} Technology General Ves (Control4 Certified, AMX Device Discovery, Crestron Integrated Partner, Savant Partner in Excellence, R11 & URC) General Integration Partner Crestron Integrated Partner, Savant Partner in Excellence, R11 & URC) General Lens 4K All Range Crisp Focus (ARC-F) Projection Picture Size General Features Acceptable Computer Signals fH: 19 to 72 kHz, fV: 48 to 92 Hz, fV: 60 Hz General Features Information Menu Horizontal and Vertical frequency display General Features Information Menu Horizontal and Vertical frequency display Input A D-sub 15 Pin, Analog RGB/Component Lens Control Motorized focus, shift and zoon with servo/memory Standby Mode Yes Input A Display RGB/Component Lens Control Motorized focus, shift and zoon with servo/memory Standby Mode Yes Inputs and Outputs ZiV Trigger Output(s) Art kilohms Power Off: OV (Two, selectable power / anamorphic zoom.) Inputs and Outputs HDMI TM Connection(s) (Total) 20 (Side): 1 (RCAx3), 1 (15 Pin HD) Inputs and Outputs HDMI TM Connection(s) (Total)	Display	Aspect Ratio	17:9
Display Features Display Technology SXRD TM Technology Ceneral Ves (Control4 Certified, AMX Device Discovery, Certistron Integrated Partner, Savant Partner in Excellence, RTI & URC) General Integration Partner Ves (Control4 Certified, AMX Device Discovery, Certistron Integrated Partner, Savant Partner in Excellence, RTI & URC) Ceneral Features 4K All Range Crisp Focus (ARC-F) Projection Picture Size 40° to 300° measured diagonally Ceneral Features Acceptable Computer Signals ft: 19 to 72 kHz, fV: 48 to 92 Hz, fV: 60 Hz Information Menu Horizontal and Vertical frequency display Input A D-sub 15 Pin, Analog RGB/Component Lens Control Motorized focus, shift and zoom with servo/memory Yes (Component Video (Y/Pb/Pi) Stable Mode Ves Inputs and Outputs 12V Trigger Output(s) Mini Jack - Power On: DC 12V, output impedance: Ar kilohms Power Off: 0V (Two, selectable power / anamorphic zoom, an		Display Resolution	4096 × 2160 (Full 4K)
General Viscon of the second of	Display Features		
General Integration Partner Yes (Control A Cettified, AMX Device Discovery, Crestron Integrated Partner, Savant Partner in Excellence, RI & URC) Lens 4.4 All Range Crisp Focus (ARC-F) Projection Picture Size 60" to 300" measured diagonally Ceneral Features 4.4 All Range Crisp Focus (ARC-F) Information Menu Horizontal and Vertical frequency display Input A D-sub 15 Pin, Analog RB/Component Lens Control Motorized focus, shift and zoom with servo/memory Standby Mode Ves Inputs and Outputs 12V Trigger Output(s) Mini Jack - Power On: DC 12V, output impedance: 4.7 kilohms Power Off: 0V (Two, selectable power / anamorphic zoom.) 3D Sync 1 (Side) RJ45 Component Video (Y/Pb/Pr) Input(s) 2 (Side): 1 (RCAx3), 1 (15 Pin HD) Input(s) 1 (Side) RJ45 Component Video (Y/Pb/Pr) Input(s) 2 (Side) Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support ¹ Renote Network Connection(s) 1 (Side) Mini Jack PC Video Input(s) 2 (Side) Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support ¹ Renote Network Connection(s) 1 (Side) RJ45, 10 base-T/100base-T Renote Network Connection(s) 1 (Side) RJ45, 10 base-T/100base-T	Display Features	Display Technology	SXRD™ Technology
GeneralIntegration PartnerCrestrelence, RTI & URC) Exclence, RTI & URC)GeneralEns4K All Range Crisp Focus (ARC-F) Projection Picture Size000 measured diagonallyCeneral FeaturesAcceptable Computer SignalsfH: 19 to 72 kHz, fV: 48 to 92 Hz, fV: 60 HzGeneral FeaturesInformation MenuHorizontal and Vertical frequency displayGeneral FeaturesInput AD-sub 15 Pin, Analog RGB/ComponentLens ControlMotorized focus, shift and zoom with servo/memory Standby ModeYesInputs and Outputs12V Trigger Output(s)Art kilohms Power On: DC 12V, output Impedance: Art kilohms Power Off: OV (Two, selectable power/ anamorphic zoom.)Inputs and Outputs12V Trigger Output(s)1 (Side) RJ45Inputs and OutputsGonponent Video (V/Pb/Ph) Input(s)2 (Side) Digital RGB/V/Cb(Pb)Cr(Pr) with PC timing supportiInputs and OutputsHDMIM Connection(s) (Total)2 (Side) Digital RGB/V/Cb(Pb)Cr(Pr) with PC timing supportiInputs and OutputsKI Input(s)1 (Side) RJ-45, 10 base-T/100base-T Remote Network Connection(s) (Total)2 (Side) RJ-45, 10 base-T/100base-T Remote Network Connection(s)Remote Network Connection(s)1 (Side) RJ-45, 10 base-T/100base-T Res22 C Input(s)Psub Spin (female)Coptional AccessoriesOptional AccessoriesVitra High Pressure Replacement Lamp (LMP-H330)	General		
Lens 4K All Range Crisp Focus (ARC-F) Projection Picture Size 60" to 300" measured diagonally General Features Information Menu Hr 19 to 72 kHz, fV: 48 to 92 Hz, fV: 60 Hz Information Menu D-sub 15 Pin, Analog RGB/Component Lens Control Motorized focus, shift and zoom with servo/memory Standby Mode Yes Inputs and Outputs 12V Trigger Output(s) Mini Jack - Power On: DC 12V, output impedance: 4.7 kilohms Power Off: 0V (Two, selectable power / anamorphic zoom), Inputs and Outputs 12V Trigger Output(s) 1 (Side) RJ45 Component Video (Y/Pb/Pr) Input(s) 2 (Side): 1 (RCAx3), 1 (15 Pin HD) Inputs and Outputs HDMI™ Connection(s) (Total) 2 (Side): Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support ¹ Inputs and Outputs HDMI™ Connection(s) (Total) 2 (Side) Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support ¹ Inputs and Outputs FC Video Input(s) D-sub 15-pin Remote Network Connection(s) 1 (Side) Min Jack PC Video Input(s) Desub 15-pin Remote Network Connection(s) 1 (Side) RJ45, 10 base-T/100base-T Re322 Control Yes Optional Accessories	Coperal	Integration Partner	Crestron Integrated Partner, Savant Partner in
General Features Acceptable Computer Signals fH: 19 to 72 kHz, fV: 48 to 92 Hz, fV: 60 Hz Information Menu Horizontal and Vertical frequency display Input A D-sub 15 Pin, Analog RGB/Component Lens Control Motorized focus, shift and zoom with servo/memory Standby Mode Yes Inputs and Outputs 12V Trigger Output(s) 4.7 kilohms Power On: DC 12V, output impedance: 3D Sync 1 (Side) RJ45 Component Video (Y/Pb/Pr) 2 (Side): 1 (RCAx3), 1 (15 Pin HD) Inputs and Outputs HDMI™ Connection(s) (Total) 2 (Side) Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support ¹ Input(s) 1 (Side) RJ45, 1 (Side) Mini Jack PC Video Input(s) 2 (Side) Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support ¹ Input(s) 1 (Side) RJ45, 1 (Side) Mini Jack PC Video Input(s) D-sub 15-pin Remote Network Connection(s) 1 (Side) Mini Jack PC Video Input(s) D-sub 15-pin Remote Network Connection(s) 1 (Side) RJ-45, 10 base-T/100base-T RS-232C Input(s) D-sub 9-pin (female) RS232 Control Yes Yes Optional Accessories Optional Accessories		Lens	4K All Range Crisp Focus (ARC-F)
Acceptable Computer SignalsfH: 19 to 72 kHz, fV: 48 to 92 Hz, fV: 60 HzInformation MenuHorizontal and Vertical frequency displayInput AD-sub 15 Pin, Analog RGB/ComponentLens ControlMotorized focus, shift and zoom with servo/memoryStandby ModeYesInputs and OutputsInputs and Outputs12V Trigger Output(s)Mini Jack - Power On: DC 12V, output impedance: 4.7 kilohms Power Off: 0V (Two, selectable power / anamorphic zoom.)3D Sync1 (Side) RJ45Component Video (Y/Pb/Pr) Input(s)2 (Side): 1 (RCAx3), 1 (15 Pin HD)Inputs and OutputsHDMI™ Connection(s) (Total)Input(s)1 (Side) Mini JackPower Off: 0V (Two, selectable power / anamorphic zoom.)Inputs and OutputsHDMI™ Connection(s) (Total)Remote Network Connection(s)1 (Side) Mini JackPower Off: 0V (Pb)Cr(Pr) with PC timing supportiInput(s)D-sub 15-pinRemote Network Connection(s)1 (Side) RJ-45, 10 base-T/100base-TR5-232C Input(s)D-sub 9-pin (female) R232 ControlPotional AccessoriesOptional AccessoriesOptional AccessoriesOptional Accessories		Projection Picture Size	60" to 300" measured diagonally
General FeaturesInformation MenuHorizontal and Vertical frequency displayInput AD-sub 15 Pin, Analog RGB/ComponentLens ControlMotorized focus, shift and zoom with servo/memoryStandby ModeYesInputs and OutputsInputs and OutputsI2V Trigger Output(s)Al Si D Sync1 (Side) RJ45Component Video (Y/Pb/Pr)2 (Side): 1 (RCAx3), 1 (15 Pin HD)Inputs and OutputsHDMI™ Connection(s) (Total)Input(s)1 (Side) Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support1IR Input(s)1 (Side) Mini JackPC Video Input(s)1 (Side) Mini JackRemote Network Connection(s)1 (Side) RJ45, 10 base-T/100base-TRes232 ControlYesOptional AccessoriesOptional AccessoriesOptional AccessoriesOptional AccessoriesInformation MenuVes	General Features		
General FeaturesInput AD-sub 15 Pin, Analog RGB/ComponentLens ControlMotorized focus, shift and zoom with servo/memoryStandby ModeYesInputs and OutputsInputs and OutputsMini Jack - Power On: DC 12V, output impedance: 4.7 kilohms Power Off: OV (Two, selectable power / anamorphic zoom.)Inputs and OutputsI2V Trigger Output(s)A.7 kilohms Power Off: OV (Two, selectable power / anamorphic zoom.)Inputs and OutputsComponent Video (Y/Pb/Pf) Input(s)2 (Side): 1 (RCAx3), 1 (15 Pin HD)Inputs and OutputsHDMIM Connection(s) (Total)2 (Side) Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support!Inputs and OutputsHDMIM Connection(s) (Total)2 (Side) Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support!Inputs and OutputsHDMIM Connection(s) (Total)1 (Side) Mini JackRemote Network Connection(s)I (Side) RJ-45, 10 base-T/100base-TRS-232C Input(s)D-sub 15-pinRS-232C Input(s)D-sub 9-pin (female) RS232 ControlVertional AccessoriesOptional AccessoriesUltra High Pressure Replacement Lamp (LMP-H330)		Acceptable Computer Signals	fH: 19 to 72 kHz, fV: 48 to 92 Hz, fV: 60 Hz
Lens ControlMotorized focus, shift and zoom with servo/memoryStandby ModeYesInputs and OutputsI2V Trigger Output(s)Mini Jack - Power On: DC 12V, output impedance: 4.7 kilohms Power Off: 0V (Two, selectable power / anamorphic zoom.)I2V Trigger Output(s)1 (Side) RJ45I2V Trigger Output(s)2 (Side): 1 (RCAx3), 1 (15 Pin HD)Inputs and OutputsHDMI ^M Connection(s) (Total)2 (Side) Digital RGB/Y/Cb(Pb)Cr(Pf) with PC timing support ¹ IR Input(s)1 (Side) Mini JackPC Video Input(s)0.5ub 15-pinRemote Network Connection(s)1 (Side) RJ-45, 10 base-T/100base-TRes22 ControlVesVesOptional AccessoriesOptional AccessoriesUttra High Pressure Replacement Lamp (LMP-H330)		Information Menu	Horizontal and Vertical frequency display
Standby ModeYesInputs and OutputsMini Jack - Power On: DC 12V, output impedance: 4.7 kilohms Power Off: DV (Two, selectable power / anamorphic zoom.)3D Sync1 (Side) RJ45Component Video (Y/Pb/Pr) input(s)2 (Side): 1 (RCAx3), 1 (15 Pin HD)Inputs and OutputsHDMI™ Connection(s) (Total)2 (Side) Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support1Inputs and OutputsFC Video Input(s)D-sub 15-pinInput(s)1 (Side) RJ-45, 10 base-T/100base-TRemote Network Connection(s)1 (Side) RJ-45, 10 base-T/100base-TRS-232C Input(s)D-sub 9-pin (female)RS232 ControlYesOptional AccessoriesOptional AccessoriesUltra High Pressure Replacement Lamp (LMP-H330)	General Features	Input A	D-sub 15 Pin, Analog RGB/Component
Inputs and Outputs Mini Jack - Power On: DC 12V, output impedance: 4.7 kilohms Power Off: 0V (Two, selectable power / anamorphic zoom.) 3D Sync 1 (Side) RJ45 Component Video (Y/Pb/Pr) Input(s) 2 (Side): 1 (RCAx3), 1 (15 Pin HD) HDMI TM Connection(s) (Total) 2 (Side) Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support ¹ IR Input(s) 1 (Side) Mini Jack PC Video Input(s) D-sub 15-pin Remote Network Connection(s) 1 (Side) RJ-45, 10 base-T/100base-T RS-232C Input(s) D-sub 9-pin (female) RS232 Control Yes Optional Accessories Optional Accessories Ultra High Pressure Replacement Lamp (LMP-H330)		Lens Control	Motorized focus, shift and zoom with servo/memory
Inputs and Outputs Inputs and Outputs Inputs and Outputs Inputs Inputs Inputs		Standby Mode	Yes
I2V Trigger Output(s)4.7 kilohms Power Off: 0V (Two, selectable power / anamorphic zoom.)3D Sync1 (Side) RJ45Component Video (Y/Pb/Pr) Input(s)2 (Side): 1 (RCAx3), 1 (15 Pin HD)HDMI™ Connection(s) (Total)2 (Side) Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support1IR Input(s)1 (Side) Mini JackPC Video Input(s)D-sub 15-pinRemote Network Connection(s)1 (Side) RJ-45, 10 base-T/100base-TRS-232C Input(s)D-sub 9-pin (female)RS232 ControlYesOptional AccessoriesOptional AccessoriesInput AccessoriesItra High Pressure Replacement Lamp (LMP-H330)	Inputs and Outputs		
Inputs and OutputsComponent Video (Y/Pb/Pr) Input(s)2 (Side): 1 (RCAx3), 1 (15 Pin HD)Inputs and OutputsHDMI™ Connection(s) (Total)2 (Side) Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support1IR Input(s)1 (Side) Mini JackPC Video Input(s)D-sub 15-pinRemote Network Connection(s)1 (Side) RJ-45, 10 base-T/100base-TRS-232C Input(s)D-sub 9-pin (female)RS232 ControlYesOptional AccessoriesOptional AccessoriesOptional AccessoriesOptional Accessories		12V Trigger Output(s)	4.7 kilohms Power Off: 0V (Two, selectable power /
Inputs and OutputsHDMI™ Connection(s) (Total)2 (Side). F (RCAX3), F (TS FIFTED)Inputs and OutputsHDMI™ Connection(s) (Total)2 (Side). Digital RGB/Y/Cb(Pb)Cr(Pr) with PC timing support1IR Input(s)1 (Side) Mini JackPC Video Input(s)D-sub 15-pinRemote Network Connection(s)1 (Side) RJ-45, 10 base-T/100base-TRS-232C Input(s)D-sub 9-pin (female)RS232 ControlYesOptional AccessoriesOptional AccessoriesUltra High Pressure Replacement Lamp (LMP-H330)	Inputs and Outputs	3D Sync	1 (Side) RJ45
In puts and Outputs HDMItM Connection(s) (Total) support1 IR Input(s) 1 (Side) Mini Jack PC Video Input(s) D-sub 15-pin Remote Network Connection(s) 1 (Side) RJ-45, 10 base-T/100base-T RS-232C Input(s) D-sub 9-pin (female) RS232 Control Yes Optional Accessories Optional Accessories			2 (Side): 1 (RCAx3), 1 (15 Pin HD)
PC Video Input(s) D-sub 15-pin Remote Network Connection(s) 1 (Side) RJ-45, 10 base-T/100base-T RS-232C Input(s) D-sub 9-pin (female) RS232 Control Yes Optional Accessories Optional Accessories Optional Accessories VItra High Pressure Replacement Lamp (LMP-H330)		HDMI™ Connection(s) (Total)	
PC Video Input(s) D-sub 15-pin Remote Network Connection(s) 1 (Side) RJ-45, 10 base-T/100base-T RS-232C Input(s) D-sub 9-pin (female) RS232 Control Yes Optional Accessories Optional Accessories Optional Accessories VItra High Pressure Replacement Lamp (LMP-H330)		IR Input(s)	1 (Side) Mini Jack
Remote Network Connection(s) 1 (Side) RJ-45, 10 base-T/100base-T RS-232C Input(s) D-sub 9-pin (female) RS232 Control Yes Optional Accessories Ultra High Pressure Replacement Lamp (LMP-H330)			
RS-232C Input(s) D-sub 9-pin (female) RS232 Control Yes Optional Accessories Optional Accessories Optional Accessories Ultra High Pressure Replacement Lamp (LMP-H330)		Remote Network Connection(s)	
RS232 Control Yes Optional Accessories Ves Optional Accessories Ultra High Pressure Replacement Lamp (LMP-H330)			
Optional Accessories Optional Accessories Ultra High Pressure Replacement Lamp (LMP-H330)			
Optional Accessories Optional Accessories Ultra High Pressure Replacement Lamp (LMP-H330)	Optional Accessories		
	Optional Accessories	Optional Accessories	Ultra High Pressure Replacement Lamp (LMP-H330)
		·	

SONY

Accessories	Supplied Accessories	Remote Control (RM-PJ22) Instruction Manual AC Cord Size AA batteries x 2 (2) 3D Glasses: TDG-PJ1
Service and Warranty Information		
Service and Warranty Information	Limited Warranty Term	Product Warranty - Limited 3 Years Parts and Labor except the lamp. Lamp Warranty - 90 Days from date of purchase.
TV System		
TV System	Color System	Auto, NTSC, PAL, SECAM
Video		
	Brightness	2000 Lumens
	Contrast Ratio	1,000,000:1 Dynamic Contrast
Video	Deep Color	Yes
Video	Picture Modes	9 modes
	Video Calibration Settings	11 Gamma Modes Independent settings for 2D & 3D viewing
Video Features		
	3D Anamorphic	Yes, via picture position or external lens
Video Features	4K resolution upscaling	Yes - 3840 x 2160 (QFHD)
	Acceptable Video Signals	480/60i, 576/50i, 480/60p, 576/50p,720/60p, 720/50p, 1080/60i, 1080/50i The following items are available for HDMI input only: 1080/60p, 1080/50p, 1080/24p,3840 x 2160/24p, 3840 x 2160/25p, 3840 x 2160/30p, 3840 x 2160/60p, 4096 x 2160/24p, 4096 x 2160/60p
	Anamorphic	Yes, lens-less anamorphic via picture position
	Deep Color	Yes
	Film Mode	Yes
	Lens Shift Function	Yes 80(v), 30(h)
	Motionflow™ Technology	Yes (120 Hz with Dark Frame Insertion)
	Picture Position	Yes, 5 Modes (including lens-less anamorphic)
	Pixel Alignment	Yes, 0.1 Pixel increments, 153 zones
	Title Area Control	Yes
	Vertical Position	Yes
	Video Processing	Optional
	Wide Mode	Yes
	x.v.Color™ Technology	Yes
	Color Space	Supports sRGB (Rec 709), DCI, Adobe RGB

1. Requires 3D content, 3D player, 3D glasses, and HDMI® cable (at least 10.2 Gbps).

2. Simulated 3D image will vary based on source content.

3. Ethernet connection required. Fees may apply for 4K networked video service.

4. Lamp in this product contains mercury. Disposal of these materials may be regulated due to environmental considerations. For disposal or recycling information, please contact your local authorities or the Telecommunications Industry Association (www.elae.org).

© 2013 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice.